



22141 U.S. PTO
10/762376
012304



INVESTOR IN PEOPLE

The Patent Office
Concept House
Cardiff Road
Newport
South Wales
NP10 8QQ

I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.

Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.

Signed

Dated

13 January 2004

THIS PAGE BLANK

OLIFF & BERRIDGE, PLC

P.O. BOX 19928

ALEXANDRIA, VA 22320

(703) 836-6400


APPLICANT: Ian S. BREAKWELL et al.

APPLICATION NO.: New U.S. Application

FILED: January 23, 2004

FOR: A GAS TURBINE ENGINE NOSE CONE

ATTORNEY DOCKET NO.: 118450



Statement of inventorship and of right to grant of a patent

The Patent Office

Cardiff Road
Newport
South Wales
NP10 8QQ

1. Your reference DY 3091

2. Patent application number
(if you know it)

0303569.8

3. Full name of the or of each applicant ROLLS-ROYCE plc

4. Title of the invention

A GAS TURBINE ENGINE NOSE CONE

5. State how the applicant(s) derived the right from the inventor(s) to be granted a patent

BY VIRTUE OF AN ASSIGNMENT DATED 6 FEBRUARY 2003

6. How many, if any, additional Patents Forms 7/77 are attached to this form?
(see note (c))

NO

7.

I/We believe that the person(s) named over the page (and on any extra copies of this form) is/are the inventor(s) of the invention which the above patent application relates to.

Signature

Date

M A GUNN

13 FEBRUARY 2003

8. Name and daytime telephone number of person to contact in the United Kingdom

ANDREW LITTLE 01332 249397
t.little@rolls-royce.com

Notes

- If you need help to fill in this form or you have any questions, please contact the Patent Office on 08459 500505.
- Write your answers in capital letters using black ink or you may type them.
- If there are more than three inventors, please write the names and addresses of the other inventors on the back of another Patents Form 7/77 and attach it to this form.
- When an application does not declare any priority, or declares priority from an earlier UK application, you must provide enough copies of this form so that the Patent Office can send one to each inventor who is not an applicant.
- Once you have filled in the form you must remember to sign and date it.

Patents Form 7/77

Enter the full names, addresses and postcodes of the inventors in the boxes and underline the surnames

IAN STEPHEN BREAKWELL
BRUNT HOUSE
53 CROSSHILL
CODNOR
RIPLEY
DERBYSHIRE
DE5 9SQ

Patents ADP number (if you know it):

8670591001

ROBERT JOHN FARNDON
6 FOXDELL WAY
CHELLASTON
DERBY
DE73 1PU


Patents ADP number (if you know it):

8566945001

Reminder

Have you signed the form?

Patents ADP number (if you know it):



Request for grant of a patent

(See the notes on the back of this form. You can also get an explanatory leaflet from the Patent Office to help you fill in this form)

The Patent Office

Cardiff Road
Newport
South Wales
NP10 8QQ

1. Your reference DY 3091

2. Patent application number

(The Patent Office will fill in this part)

0303569.8

3. Full name, address and postcode of the or of each applicant (underline all surnames)

ROLLS-ROYCE plc
65 BUCKINGHAM GATE
LONDON
SW1E 6AT
GREAT BRITAIN

Patents ADP number (if you know it)

If the applicant is a corporate body, give the country/state of its incorporation

GREAT BRITAIN

8504375001

4. Title of the invention A GAS TURBINE ENGINE NOSE CONE

5. Name of your agent (if you have one)

"Address for service" in the United Kingdom to which all correspondence should be sent (including the postcode)

M A GUNN
ML-9
ROLLS-ROYCE plc
PO BOX 31
DERBY
DE24 8BJ

Patents ADP number (if you know it)

3962003

6. If you are declaring priority from one or more earlier patent applications, give the country and the date of filing of the or of each of these earlier applications and (if you know it) the or each application number

Country

Priority application number
(if you know it)

Date of filing
(day / month / year)

7. If this application is divided or otherwise derived from an earlier UK application, give the number and the filing date of the earlier application

Number of earlier application

Date of filing
(day / month / year)

8. Is a statement of inventorship and of right to grant of a patent required in support of this request? (Answer 'Yes' if:

YES

a) any applicant named in part 3 is not an inventor, or
b) there is an inventor who is not named as an applicant, or

c) any named applicant is a corporate body.
See note (d))

Patents Form 1/77

9. Enter the number of sheets for any of the following items you are filing with this form. Do not count copies of the same document

Continuation sheets of this form 0

Description 6

Claim(s) 2

Abstract 1

Drawing(s) 2 + 2 *PK*

10. If you are also filing any of the following, state how many against each item.

Priority documents 0

Translations of priority documents 0

Statement of inventorship and right to grant of a patent (Patents Form 7/77) YES

Request for preliminary examination and search (Patents Form 9/77) YES

Request for substantive examination (Patents Form 10/77) YES

Any other documents (please specify) NO

11. I/We request the grant of a patent on the basis of this application.

Signature

M A Gunn

Date

M A GUNN

13 FEBRUARY 2002

12. Name and daytime telephone number of person to contact in the United Kingdom ANDREW LITTLE 01332 249397
t.little@rolls-royce.com

Warning

After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least 6 weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been revoked.

Notes

- If you need help to fill in this form or you have any questions, please contact the Patent Office on 08459 500505.
- Write your answers in capital letters using black ink or you may type them.
- If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.
- If you have answered 'Yes' Patents Form 7/77 will need to be filed.
- Once you have filled in the form you must remember to sign and date it.
- For details of the fee and ways to pay please contact the Patent Office.

DUPLICATE

A GAS TURBINE ENGINE NOSE CONE

The present invention relates to a gas turbine engine nose cone, particularly a turbofan gas turbine engine nose cone.

It is known from EP1016588A to provide a gas turbine engine nose cone comprising a spinner having a generally conical upstream portion and a generally cylindrical base portion having a flange removably connected to a fan hub of the gas turbine engine. A frustoconical fairing surrounds the base portion of the spinner and the outer surface of the fairing forms a continuation of the outer surface of the conical upstream portion of the spinner.

It is known from GB2011542A to provide a skin on the outer surface of a gas turbine engine nose cone to protect the nose cone from erosion.

A protective skin has been provided on the outer surface of a fairing of a nose cone comprising a spinner and a fairing, as discussed above. However, the fairing suffers from stripping of the protective skin from the upstream edge of the fairing in operation due to erosion. The protective skin peels off the fairing from the upstream end towards the downstream end in operation of the gas turbine engine due to centrifugal force.

It is known from EP1227036A to provide a circumferentially extending protective member extending around the upstream end of the fairing to retain the protective skin on the upstream end of the fairing. The protective skin for example comprises a polyurethane coating and the protective member comprises a silicone elastomer. The protective member is adhesively bonded to the fairing and the protective skin.

However, it has been found that there is insufficient adhesion between the protective member and the protective skin, which may lead to the protective member becoming detached from

the protective coating. Also, the protective skin has insufficient thickness at the upstream end of the fairing.

Accordingly the present invention seeks to provide a novel gas turbine engine nose cone which reduces, preferably overcomes, the above mentioned problems.

Accordingly the present invention provides a gas turbine engine nose cone comprising a spinner having a generally tapering upstream portion and a generally cylindrical base portion, the cylindrical base portion having a flange removably connected to a fan hub of the gas turbine engine, a tapering fairing surrounding the base portion of the spinner, the outer surface of the fairing forms a continuation of the outer surface of the tapering upstream portion of the spinner, a circumferentially extending fibrous material extending around the upstream end of the fairing, the outer surface of the fairing having a skin to protect the fairing from erosion, the skin extending around the upstream end of the fairing and being infiltrated into the fibrous material to form a composite material and to bond the skin to the upstream end of the fairing.

Preferably the skin comprises polyurethane.

Preferably a radially inner portion of the fibrous material locates in an annular groove on the radially inner surface of the upstream end of the fairing.

Preferably the circumferentially extending fibrous material is bonded to the upstream end of the fairing.

Preferably the fairing comprises a fibre-reinforced material. Preferably the spinner comprises a fibre-reinforced material. Preferably the fairing comprises a radially inwardly extending lip to form a seal between the upstream end of the fairing and the spinner.

The present invention will be more fully described by way of example with reference to the accompanying drawings in which:-

Figure 1 shows a turbofan gas turbine engine comprising a gas turbine engine nose cone according to the present invention.

Figure 2 is an enlarged cross-sectional view of the gas turbine engine nose cone shown in figure 1.

Figure 3 is a further enlarged cross-sectional view of part of the gas turbine engine nose cone shown in figure 2.

A turbofan gas turbine engine 10, as shown in figure 1, comprises in axial flow series an inlet 12, a fan section 14, a compressor section 16, a combustion section 18, a turbine section 20 and an exhaust nozzle 22. The turbine section 18 comprises a low pressure turbine (not shown) arranged to drive the fan section 14 via a shaft (not shown). The turbine section 18 also comprises a high pressure turbine (not shown) arranged to drive a high-pressure compressor (not shown) in the compressor section 16 via a shaft (not shown). The turbine section 18 may also comprise an intermediate pressure turbine (not shown) arranged to drive an intermediate pressure compressor (not shown) in the compressor section 16 via a shaft (not shown). The turbofan gas turbine engine 10 operates quite conventionally and its operation will not be discussed further.

The fan section 14 comprises a fan rotor 24 carrying a plurality of circumferentially spaced radially outwardly extending fan blades 26. The fan rotor 24 and fan blades 26 are surrounded by a fan casing 28 which partially defines a fan duct 30. The fan casing 28 is secured to a core casing 32 by a plurality of circumferentially spaced and radially extending fan outlet guide vanes 34. The fan duct 30 has a fan outlet 36 at its downstream end.

The fan rotor 24 comprises a fan disc 38 and a nose cone 40, as shown more clearly in figure 2. The fan blades 26 and nose cone 40 are mounted on the fan disc 38. The nose cone 40 is generally of a tapering shape with a point at the upstream end 42 and a circular base portion at the downstream end 44. The nose cone 40 may be either conical, dome shaped or any other

suitable shape. The nose cone 40 comprises a spinner 46 and a fairing 48.

The spinner 46 comprises a tapering upstream portion 50 and a generally cylindrical base portion 52. The cylindrical base portion 52 comprises a radially outwardly extending flange 54 which is removably connected to the fan disc 38. The tapering upstream portion 50 is preferably conical, but may be dome shaped or other suitable shapes. The tapering upstream portion 50 of the spinner 46 has an outer surface 56. The cylindrical base portion 52 is connected to the fan disc 38 by fasteners, for example bolts 58 and nuts 60. The bolts 58 extend axially through apertures 62 in the flange 54 and apertures 66 in a radially outwardly extending flange 64 on the fan disc 38. The spinner 46 preferably comprises a fibre-reinforced material, but may comprise titanium or other suitable lightweight material.

The fairing 48 tapers and surrounds the base portion 52 of the spinner 46. The outer surface 68 of the fairing 48 forms a continuation of the outer surface 56 of the tapering upstream portion 50 of the spinner 46. The fairing 48 is preferably frustoconical, but other suitable shapes may be used. The fairing 48 is removably connected to the fan disc 38 by a number of circumferentially spaced L-shaped brackets 70. Each L-shaped bracket 70 is secured to the fairing 38 by fasteners, for example bolts 72 and nuts 74. The bolts 72 extend radially through apertures 76 in the fairing 48 and apertures 78 in the L-shaped brackets 70. The bolts 72 have conical heads and the apertures 76 are countersunk. The fairing 48 preferably comprises a fibre-reinforced material, but may comprise titanium or other suitable lightweight material.

A skin 80 is provided on the outer surface 68 of the fairing 48 to protect the fairing 48 from erosion from particles entering the inlet 12 of the turbofan gas turbine engine 10. Preferably the skin 80 comprises polyurethane, but may comprise other suitable materials. The skin 80 extends from the upstream

end 82 to the downstream end 84 of the fairing 48 and the skin 80 also extends around the upstream end 82 of the fairing 48 into an annular groove 90 on the radially inner surface 92 at the upstream end 82 of the fairing 48. The skin 80 extends circumferentially through the full extent of the fairing 48.

A fibrous material 86 extends around the upstream end 82 of the fairing 48 to retain the skin 80 on the upstream end 82 of the fairing 48 and the fibrous material 86 is incorporated into the skin 80 at the upstream end 82 of the fairing 48. The fibrous material 86 reinforces the skin 80 and bonds the skin 80 to the upstream end 82 of the fairing 48, as shown more clearly in figure 3. The fibrous material 86 extends circumferentially through the full extent of the fairing 48. A radially inner portion 88 of the fibrous material 86 locates in the annular groove 90 on the radially inner surface 92 at the upstream end 82 of the fairing 48. An adhesive 94 is used to bond the fibrous material 86 into the annular groove 90 at the upstream end 82 of the fairing 48 and to the outer surface 68 of the fairing 48 at the upstream end 82 of the fairing 48. The fibrous material 86 preferably comprises a fabric of fibres, for example knitted or woven fibres. The fibres are polyester fibres, but glass fibres or other suitable fibres may be used. The adhesive 94 comprises silcoset (trade name), or an adhesive 3145 supplied by Dow Corning, but may comprise any other suitable adhesive.

The fibrous material 86 is bonded to the upstream end 82 of the fairing 48 before the skin 80 is applied to the outer surface 68 and upstream end 82 of the fairing 48. The skin 80 is applied onto the outer surface 68 of the fairing 48 and to the fibrous material 86. The skin 80 infiltrates, soaks, into the fibrous material 86 to form a composite material at the upstream end 82 of the fairing 48 and the fibrous material 86 bonds the skin 80 to the upstream end 82 of the fairing 48 and enables a skin 80 of sufficient thickness to be produced at the

upstream end 82 of the fairing 48. The fibrous material 86 provides a sufficiently large radius of curvature for the skin 80 to adhere to.

In operation the fibrous material 86 reinforces the skin 80, increases the thickness of the skin 80, bonds the skin 80 to upstream end 82 of the fairing 48 and provides greater erosion resistance to the particles that enter the inlet 12 of the turbofan gas turbine engine 10 and impact on the leading edge of the fairing 48 to reduce lifting of the skin 80 away from the leading edge 82 of the fairing 48. This ensures that the centrifugal force on the fairing 48 and skin 80 does not lead to the subsequent peeling of the skin 80 away from the fairing 48. The fairing 48 is protected from erosion for longer periods of time before a new skin 80 has to be provided on the fairing 80.

The spinner 46 may also be provided with a skin to protect against erosion from particles entering the inlet 12 of the gas turbine engine 10.

CLAIMS

1. A gas turbine engine nose cone comprising a spinner having a generally tapering upstream portion and a generally cylindrical base portion, the cylindrical base portion having a flange removably connected to a fan hub of the gas turbine engine, a tapering fairing surrounding the base portion of the spinner, the outer surface of the fairing forms a continuation of the outer surface of the tapering upstream portion of the spinner, a circumferentially extending fibrous material extending around the upstream end of the fairing, the outer surface of the fairing having a skin to protect the fairing from erosion, the skin extending around the upstream end of the fairing and being infiltrated into the fibrous material to form a composite material and to bond the skin to the upstream end of the fairing.
2. A gas turbine engine nose cone as claimed in claim 1 wherein the skin comprises polyurethane.
3. A gas turbine engine nose cone as claimed in claim 1 or claim 2 wherein the circumferentially extending fibrous material comprises woven fibres or knitted fibres.
4. A gas turbine engine nose cone as claimed in claim 1, claim 2 or claim 3 wherein a radially inner portion of the circumferentially extending fibrous material locates in an annular groove on the radially inner surface of the upstream end of the fairing.
5. A gas turbine engine nose cone as claimed in claim 4 wherein the circumferentially extending fibrous material is bonded to the upstream end of the fairing.
6. A gas turbine engine nose cone as claimed in any of claims 1 to 5 wherein the fairing comprises a fibre-reinforced material.

7. A gas turbine engine nose cone as claimed in any of claims 1 to 6 wherein the spinner comprises a fibre-reinforced material.

8. A gas turbine engine nose cone as claimed in any of claims 1 to 7 wherein a radially inner portion of the skin locates in the annular groove on the radially inner surface of the upstream end of the fairing.

9. A gas turbine engine nose cone as claimed in any of claims 1 to 8 wherein the fibrous material comprises glass fibres or polyester fibres.

10. A gas turbine engine nose cone substantially as hereinbefore described with reference to figures 1, 2 and 3 of the accompanying drawings.

ABSTRACT

A GAS TURBINE ENGINE NOSE CONE

A gas turbine engine nose cone (44) comprises a spinner (46) and a fairing (48). The spinner (46) has a conical upstream portion (50) and a cylindrical base portion (52). The fairing (48) is frustoconical and surrounds the base portion (52) of the spinner (46). The outer surface (68) of the fairing (48) forms a continuation of the outer surface (56) of the conical upstream portion (50) of the spinner (46). A fibrous material (86) extends around the upstream end (82) of the fairing (48). The outer surface (68) of the fairing (48) has a skin (80) to protect the fairing (48) from erosion. The skin (80) extends around the upstream end (82) of the fairing (48), and is infiltrated into the fibrous material (86) to form a composite material and to bond the skin (80) to the upstream end (82) of the fairing (48).

(Figure 3)

THIS PAGE BLANK (USP10)

Fig. 1.






Fig. 3.



THIS PAGE BLANK (USPTO)

Fig.2.



THIS PAGE BLANK (USPTO)